


CRYSTAL UNITS



CXAN-321 SERIES

CERAMIC PACKAGE

Applications

- DVR
- Wireless
- Camera
- Communication
- Medical
- Telecom
- Industry Control
- IoT

Features

- Seam Seal
- High Frequency Stability
- Excellent Solderability
- Excellent Thermal Hysteresis
- Excellent Vibration Resistance & Shock Resistance
- RoHS Compliant

■ Actual Size:

Specification

MODEL

DIMENSION	(mm)	3.20 X 2.50	
FREQUENCY			
FREQUENCY RANGE (Fundamental)	MHz	8.000 ~ 64.000	
FREQUENCY RANGE (3rd Overtone)	MHz	54.000 ~ 150.000	
FREQUENCY TOLERANCE (25 °C)	ppm	± 10 ~ ± 50	
FREQUENCY STABILITY (Ref to 25 °C)	ppm	± 15 ~ ± 100	± 50 ~ ± 100
ENVIRONMENTAL CONDITION			
OPERATING TEMPERATURE RANGE	°C	- 20 ~ + 70 Or Specify (- 40 ~ + 125 is available)	- 55 ~ + 125
STORAGE TEMPERATURE RANGE	°C	- 55 ~ + 125	
AGING / YEAR	ppm	± 3	
ELECTRICAL SPECIFICATIONS			
TEST CIRCUIT		S&A 250B With π Fixture	
LOAD CAPACITANCE	pF	SERIES, 6pF to 47pF, or Specify	
DRIVE LEVEL	uW	15, 30, 50, 100, 200 or special requirement	
EQUIVALENT SERIES RESISTANCE	Ω	See Table	
SHUNT CAPACITANCE	pF	3.0 Max.	

*Specification subject to change without notice.

Equivalent Series Resistance (Ω)

Frequency Range	Mode of Operation	ESR
8.000 ~ 9.999	Fundamental	500Ω Max.
10.000 ~ 11.999	Fundamental	150Ω Max.
12.000 ~ 15.999	Fundamental	80Ω Max.
16.000 ~ 19.999	Fundamental	60Ω Max.
20.000 ~ 24.999	Fundamental	50Ω Max.
25.000 ~ 49.999	Fundamental	40Ω Max.
50.000 ~ 64.000	Fundamental	30Ω Max.
54.000 ~ 124.999	3rd Overtone	100Ω Max.
125.000 ~ 150.000	3rd Overtone	80Ω Max.

Dimension(mm)

