

SMD Voltage Controlled Oscillator

Frequency 27-30MHz

VT30M


Features

- Miniature Size
- Surface Mount Package
- Electrically Shielded
- Low Phase Noise
- Highly Linear Tuning

Description

The VT30M is a fundamental single ended oscillator designed for use in cost sensitive wireless and telemetry applications. The device has been optimized by careful selection of the bipolar transistor and varactor diode for low phase noise and high linearity tuning characteristics.

SK605 Package



Electrical Specifications, $T_A = +25^\circ\text{C}$, $V_{CC} = +5\text{V}$ (unless otherwise stated)

Parameter	Test Conditions	Units	Min.	Typ.	Max.
Frequency Rangs		MHz	27		30
Tuning Voltage (V)		V	0.5		4.5
RF Output Power	27-30MHz	dBm	9.0		13.0
Supply Voltage (VCC)		V	4.75	5	5.25
Supply Current (Icc)		mA		17	20
Phase Noise :					
	@10kHz Offset:	dBc/Hz		-110	-108
	@100kHz Offset:	dBc/Hz		-132	-129
Average Tuning Sensitivity	27-30MHz	MHz/V		3.3	
Harmonic Outputs		dBc		-4.0	
Operating Temperature Range		$^\circ\text{C}$	-40		+85
Tune Input Capacitance		PF		1000	

Comments

All specifications apply with a 50 ohm load impedance.